

Product Bulletin

Ultra Low Volume (ULV) Fogger Junior 5330, Portable

Motor: ¼ hp, 50/60 Hz, 240 VAC, 1.5 amp

Liquid Capacity: One quart (950 ml)

Chemicals: Any lightweight liquids.

Particle Size: 15 – 40 microns, adjustable

Discharge Rate: 0 – 4 oz (120 ml) / min, adjustable

Construction Materials: Nylon/Polyethylene/Brass/Vinyl

Dimensions: L x H x W.: (28 x 25 x 11 cm)

Shipping Weight: 2.0 kg



Fogging technique and application:

Small and highly maneuverable, the Junior is used for air freshening in hotel rooms, odour removal in cars, applying coil cleaners to air conditioning systems, as well as basic pest control application at home.

It can fog both water and oil based liquids. A one turn valve controls particle size in a range from a 15 micron intermediate fog to a 40 micron heavy mist. It's easy to calibrate the output rate when changing liquids. Graduated markings on the chemical solution tank provides accurate and easy reference during preparation of application solutions, be it pesticides, sanitizers, deodorants, etc.

Constructed of corrosion resistant materials, this fogger is designed for jobs where a smaller and less expensive cold fogging solution is desired.

The simple on-off switch located above the handle makes the Fogmaster Junior a truly user friendly and great utility cold fogger for any home or garden applications.

A smaller fogger for the smaller job – spot odour control, humidifying, disinfecting, local pest control and more.

Subject to technical changes 12/2007